

HRC BS TYPE FUSE LINKS 415V

BS88 CLIP IN FUSES

Rating Amp	Overall Length	Carton Qty.	Sku.No	Price \$ Schedule 'S'
Off-set Tags Clip Fixing				
2	51mm	20	SS2	15.86
4			SS4	15.86
6			SS6	15.86
10			SS10	15.86
16			SS16	19.13
20			SS20	21.03
25	62mm		SS25	21.03
2			NS2	7.52
4			NS4	7.52
6			NS6	7.52
10			NS10	7.52
16			NS16	7.52
20			NS20	9.65
25			NS25	11.16
32			NS32	11.16
10M16			NS10M16	8.83
16M20	NS16M20	8.83		
20M25	NS20M25	11.16		
20M32	NS20M32	11.16		
25M32	NS25M32	11.16		
32M40	NS32M40	18.43		
40	69mm		ES40	23.66
50			ES50	23.66
63			ES63	24.2
63M80			ES63M80	47.55

Features:

- » Standards: ASTA20 Certified, BS88-1 & 6, AS60269, IEC269-2-1
- » NS 80kA, 415V AC
40kA, 240V DC
- » ES 80kA, 440V AC



NS2

Features:

- » Standards: BS88-1 & 6, AS60269, IEC269-2-1, 415V AC
- » Part Number Suffix
- » H = Front Connected
- » P = Back Connected, 2 Stud
- » BW = Back Wired
- » BHA = Busbar Mounted
- » PH = Back connect/Front connect



SC32H

GE ENGLISH TYPE
SAFECLIP

BW TYPE

SAFECLIP FITTINGS

Rating Amp	To suit HRC Fuse Link	Sku.No	Price \$ Schedule 'S'
Colour: Black			
20	NS	SC20H	15.74
	NS	SC32H	18.07
32	NS	SC32PH-D	40.04
	NS	SC32P	35.19
	NS	SC32BW	18.07
	NS	SC32BHA	37.75
	NS	SC63H-D	43.40
63	ES	SC63H-D	43.40
Colour: White			
20	SC20/32 LINK	SC20HWH	Schedule 'S' 21.60
32	SC20/32 LINK	SC32HWH	23.53
	SC20/32 LINK	SC32PWH	40.65
Fuse Carrier for NS Fuselinks in SC63			
63	NS	SCA63NS	Schedule 'T' 18.80
Neutral Links			
20/32	SC20/32	SC20/32LINK	Schedule 'S' 6.07
20	SS20	SSCLINK	8.54
63	SC63	ESCLINK	9.70



H TYPE



PH-D TYPE



P TYPE



BHA TYPE

TYPE 'T' FOR INDUSTRIAL & GENERAL APPLICATIONS



OFFSET TAGS



NIT6L

BS88 BOLT-IN FUSES

Rating Amp	Fixing Centres	Carton Qty.	Sku.No	Price \$ Schedule'S'
Off-set Tags 2-hole Fixing				
6	38.0mm	10	LST6	7.48
10			LST10	7.48
16			LST16	7.48
20			LST20	7.48
2	44.5mm	20	NIT2L	7.94
4			NIT4L	7.94
6			NIT6L	7.94
10			NIT10L	7.94
16			NIT16L	7.94
20			NIT20L	9.09

*Note: LST Fuse Links used for street Lighting

Indent Item

TYPE 'T' FOR INDUSTRIAL & GENERAL APPLICATIONS

Rating Amp	Fixing Centres	Carton Qty.	Sku.No	Price \$ Schedule'S'
Off-set Tags 2-hole Fixing				
2	73.0mm	10	TIA2L	13.03
4			TIA4L	13.03
6			TIA6L	13.03
10			TIA10L	13.03
16			TIA16L	14.43
20			TIA20L	14.43
25			TIA25L	14.43
32			TIA32L	14.43
32M35			TIA32M35L	16.38
32M40			TIA32M40L	16.38
32M50			TIA32M50L	16.38
32M63			TIA32M63L	16.38
35			TIS35L	24.57
40			TIS40L	24.57
50	TIS50L	24.57		
63	TIS63L	24.57		
80	OS80	47.26		
100	OS100	53.38		
100M12 5	OS100M125	64.06		
63	94.0mm	5	TCP63L	47.31
80			TCP80L	47.31
100			TCP100L	47.31

TYPE 'T' FOR INDUSTRIAL & GENERAL APPLICATIONS

Rating Amp	Fixing Centres	Carton Qty.	Sku.No	Price \$ Schedule'S'
Central Tags 2-hole Fixing				
80	11mm	5	TC80L	47.31
100			TC100L	47.31
125			TF125L	72.79
160			TF160L	77.65
200			TF200L	82.5
250			TKF250L	126.71
315	TKF315L	137.12		
Central Tags 4-Hole Fixing				
355	133 /184mm	1	TM355L	169.85
400			TM400L	200.17
450			TTM450L	253.55
500			TTM500L	297.22
560			TTM560L	309.36
630			TTM630L	339.69
670			TLM670L	430.68
710			TLM710L	473.14
750			TLM750L	527.73
800			TLM800L	564.12

Features:

- » Standards: ASTA20 Certified, BS88-2,
- » AS60269, IEC269-2-1, 80kA, 415V AC
- » OS 80kA, 440V AC



TIA32L



CENTRE TAGS



TFM

TTM

HRC BS TYPE FUSE LINKS 550/660V

Features:

- » Standards: ASTA20 Certified, BS88-2, AS60269, IEC269-2-1
- » NIT = 80kA, 550V AC
- » +NET/NIT_M = 440V AC
- » T = 80kA, 660V AC



NIT6

TFP

Features:

- » Standards: ASTA20 Certified, BS88-2, AS60269, IEC 269-2-1, 80kA, 660V AC
- » 40kA, 350V/460V DC



TC



TKM

Rating Amp	Fixing Centres	Carton Qty.	Sku.No	Price \$ Schedule 'S'		
Off-set Tags 2-hole Fixing						
2	44.5mm	20	NIT2	9.41		
4			NIT4	9.41		
6			NIT6	9.41		
10			NIT10	9.41		
16			NIT16	9.41		
20			NIT20	10.29		
25			NET25+	10.29		
32			NET32+	10.29		
20M25			NIT20M25+	10.29		
20M32			NIT20M32+	10.29		
2			73.0mm	10	TIA2	17.39
4					TIA4	17.39
6					TIA6	17.39
10	TIA10	17.39				
16	TIA16	9.08				
20	TIA20	9.08				
25	TIA25	22.63				
32	TIA32	22.63				
32M35	TIA32M35	22.63				
32M40	TIA32M40	22.63				
32M50	TIA32M50	22.63				
32M63	TIA32M63	24.62				
35	TIS35	31.85				
40	TIS40	31.85				
50	TIS50	31.85				
63	TIS63	31.85				
63M80	TIS63M80	29.73				
63M100	TIS63M100	30.33				
80	94.0mm	5	TCP80	57.72		
100			TCP100	57.72		
100M12 5			TCP100M125	55.81		
100M160			TCP100M160	58.23		
100M200			TCP100M200	80.07		
12 5			TFP125	76.43		
160			TFP160	78.86		
200			TFP200	87.35		

Rating Amp	Fixing Centres	Carton Qty.	Sku.No	Price \$ Schedule 'S'		
Central Tags 2-hole Fixing						
6	97.0mm	20	TB6	27.12		
10			TB10	27.12		
16			TB16	27.12		
20			TB20	27.12		
20			TB25	27.12		
32			TB32	27.12		
35			TB35	29.09		
40			TB40	29.09		
50			TB50	29.09		
63			TB63	29.09		
6			111mm	5	TBC6	27.12
10					TBC10	27.12
16					TBC16	27.12
20	TBC20	27.12				
25	TBC25	27.12				
32	TBC32	27.12				
35	TBC35	29.09				
40	TBC40	29.09				
50	TBC50	29.09				
63	TBC63	29.09				
80	TC80	57.72				
100	TC100	57.72				
125	TF125	83.28				
160	TF160	88.5				
200	TF200	95.12				
200M250	TF200M250	94.63				
200M315	TF200M315	102.22				
250	1	TKF250	137.43			
315		TKF315	151.96			
315M355		TKF315M355	163.3			
250		TKM250	129.81			
315		TKM315	143.16			
355	111mm	TMF355	171.06			
400		TMF400	196.53			
400M450		TMF400M450	217.16			

HRC BS TYPE FUSE LINKS 660V

Features:

- » ASTA20 Certified, BS88-2, AS60269,
- » IEC 269-2-1, 80kA, 660V AC
- » 40kA, 350V/460V DC



TTM

Rating Amp	Fixing Centres	Carton Qty.	Sku.No	Price \$ Schedule'S'
Central Tags 4-Hole Fixing				
355	133/184mm	1	TM355	195.58
400			TM400	214.41
400M450			TM400M450	224.44
450			TTM450	290.45
500			TTM500	334.08
560			TTM560	359.01
630			TTM630	392.67
670			TLM670	491.15
710			TLM710	542.25
750			TLM750	585.88
800	TLM800	634.49		
355	165/229mm		TMT355	POA
400			TMT400	POA
450			TT450	POA
500			TT500	POA
560			TT560	POA
630			TT630	POA
670			TLT670	POA
710			TLT710	POA
750			TLT750	POA
800			TLT800	POA
1000	159/238mm		CLL1000	POA
1200			CLL1200	POA
1600			CLL1600	POA

CLL is equivalent to TUV range, should be used as direct replacement

Indent Item

Features:

- » ASTA20 Certified, BS88-2,
- » AS2005, IEC269-2-1, 80kA, 660V AC
- » 40kA, 300V/350V DC
- » CLL 200kA, 600V



TXU

Rating Amp	Fixing Centres	Carton Qty.	Sku.No	Price \$ Schedule'S'
Central Tags 4-Hole Fixing				
560	149mm	1	TLU560	POA
630			TLU630	POA
670			TLU670	POA
710			TLU710	POA
750			TLU750	POA
800			TLU800	POA
1000			TXU1000	POA
1250			TXU1250	POA

Indent Item

OUTDOOR 415V TYPES

Features:

- » ASTA20 Certified, BS88-2
- » IEC269-2-1, 80kA, 415V
- » Weatherproofed for outdoor applications



OTMF400

Rating Amp	Fixing Centres	Carton Qty.	Sku.No	Price \$ Schedule'S'
Central tags 2-hole fixing				
63	111	10	OTBC63	31.42
80		5	OTC80	47.93
100		OTC100	47.93	
125		OTF125	70.68	
160		OTF160	77.1	
200	133/184	1	OTF200	83.52
250			OTKF250	117.18
315			OTKF315	130.89
400			OTMF400	189.47
Central tags 4-hole fixing				
450	133/184	1	OTTM450	245.57
500			OTTM500	295.44
630			OTTM630	337.82
710			OTLM710	474.94
800			OTLM800	559.7



LV FUSE FITTINGS - REDSPOT

Features:

- » Standards: BS88-2, AS60269,
- » IEC269-2-1
- » 660V AC
- » PH = Front Connected/Back connected, 1 Stud
- » H = Front Connected
- » P = Back Connected, 2 Stud
- » BW = Back Wired



H-TYPE



PH-TYPE



P-TYPE



H TYPE WHITE



H TYPE



BW TYPE



PH TYPE



P TYPE

Rating Amp	Dimension HxWxD	To suit HRC Fuse Link	Sku.No	Price \$ Schedule'S'
Colour: Black				
20	79x27x55	NIT	RS20H	33.71
			RS20P	45.12
			RS20PH	41.12
			RS20BW	40.27
32	103x32x70	TIA	RS32H	44.28
			RS32P	59.68
			RS32PH	50.26
			RS32BW	47.26
63	110x35x75	TIS	RS63H	51.15
			RS63P	70.91
			RS63PH	64.54
			RS63BW	50.37
100	140x51x100	TCP	RS100H	118.89
			RS100P	151.87
			RS100PH	140.73
			RS100BW	120.10
200	216x70x137	TC	RS200H	327.56
			RS200P	370.02
400	254x98x192	TF	RS200PH	363.95
			RS400H	POA
		TKM	RS400P	POA
			TM	RS400PH

Rating Amp	Dimension HxWxD	To suit Link	Sku.No	Price \$ Schedule'S'
Colour: White				
20	79x27x55	RS20CLINK	RS20HWH	42.46
20	79x27x55	RS20CLINK	RS20PWH	53.38
32	103x32x70	RS32CLINK	RS32HWH	55.81
32	103x32x70	RS32CLINK	RS32PWH	74.00
63	110x35x75	RS63CLINK	RS63HWH	85.56
63	110x35x75	RS63CLINK	RS63PWH	98.54
100	140x51x100	RS100CLINK	RS100HWH	220.01
100	140x51x100	RS100CLINK	RS100PWH	296.42

Indent Item

4

